

QUICK CHECKLIST



Area to check	Checkpoint/measure	Drivers manual pict	Notice
1 A Trailer coupling wear	VBG 750/795/795VR A: not more than <math><45,7\text{mm}</math> B: not lesser than $>42,5\text{mm}$ C: not lesser than $>55,0\text{mm}$ D: marking on wear heel		
1 B Trailer coupling wear	VBG 760 A: not more than <math><49,5\text{mm}</math> B: not lesser than $>44,8\text{mm}$ C: not lesser than $>55,0\text{mm}$		
2 A Locking pin, lamp in the cabin	Safety locking pin The red locking pin stands out visible when coupling is open, red lamp is visible in the cabin		
2 B Locking pin, lamp in the cabin	Safety locking pin Locking pin is recessed when closed coupling, green lamp is visible in the cab		
3 A Drawbeam/ endplate/ drawbar	Visible damages: Deformations, cracks or other damages?		
3 B Drawbeam/ endplate	Tightening torque: M14 163 Nm, 10.9 M16 250 Nm, 10.9 (M16 MB 225 Nm)		
3 C Drawbar VBG Multi och VBG Multi XF	Tightening torque: M14 125 Nm, 8.8 M16 195 Nm, 8.8 M27 600-650 Nm		
4 A Drawbar eye 57 Swedish standard	Drawbar eye wear D-measure not more than 59,5 mm		
4 B Drawbar eye 57 Swedish standard	Drawbar eye wear T-measure not lesser than 19 mm		