

# PRETREATmaker IV

Easier, cleaner, more precise pretreat for DTG Printing

- Stepper motor for smoother, more accurate spray patterns
- Complete spray and mist containment
- One touch automated cleaning functions for easier use
- Quickly switch between two pretreatment liquids
- Lower slides with splash guards and anti-stick sliders on upper rails
- Optional open interface and barcode system easy integration with existing production systems
- Optional onboard scale for measuring fluid lay down and low supply warning
- Durable zinc and powder-coated housing
- Large spray area (16.5" x 23.5")
- Compact size (35" x 28" x 19")



Images are for illustrative purposes only.






Spraying Area	16 × 24" (40 × 60 cm)
Spraying method	Nozzles are moving over the table (inside)
Table length	31.5" (80 cm)
Spray direction	Uni / Bi-Directional
Nozzles	4 Nozzles
Number of bottles	Two Pretreat (10 L and 5 L), One Water (5 L), One Waste (5 L)
Motor	Stepper Motor
Pumps	Two
Dimensions	L 35.4" × W 28.3" × H 18.9" (L 90 × W 72 × H 48 cm)
Dimensions (transport)	L 37.4" × W 31.5" × H 24" (L 95 × W 80 × H 61 cm)
Weight	150 lbs. (68 kg)
Weight (transport)	190 lbs. (86 kg)
Barcode	Open Interface
Connection	220/230 or 110/120 VAC (automatic switch)
Consumption	150 W
Operating pressure (precoating)	max. 7 bar
Included in delivery	replacement nozzle, replacement filter and ultrasound cleaner
Additional characteristics	zinc- and powder-coated housing



1. Stainless steel spare nozzle 803427
2. Brass spare nozzle 803426
3. Stainless steel extra wide hole nozzle 803463
4. Brass extra wide hole nozzle 803380



5. Scale 807051
6. Scanner modul incl. interface 807059
7. Tube switch for precoating pump 807049

Part #: IPDCAT315C-120117

The PRETREATmaker IV is a Schulze product and Brother International Corporation makes no representations or warranties regarding such product. Improvements compared to PRETREATmaker III.

**brother**  
at your side