

FP6000 Automatic L-sealer



High performance L-sealer

The FP6000 automatic L-sealer is a highly efficient all electric sealer that can deliver high quality packaging of your garments at high speed. The FP6000 can deliver conveyor speeds up to 100 ft/min and package up to 2400 pieces per hour. The system is perfect for polyolefin or polyethylene center fold film.

Unique sealer technology

The FP6000 is designed with a film inverter, permitting product to be delivered at the sealer by conveyor. The robust single piece seal bar can seal 20" x 25" with packages up to 6" tall. This gives the FP6000 a wide variety of product height to width size choices and stores up to 20 of these in its own PLC. It has beginning and end product sensors to maintain a consistent bag length around the product. An optional shrink tunnel and pre or post conveyor is available for this system.

Easy to operate

The FP6000 can be set-up in minutes, is easy to program, and offers multiple operating modes for performance and convenience. The L-sealer does not require compressed air so it can be easily positioned in your shop and is CE compliant.

Specifications:

Power supply	208-240 3 phase 50/60Hz
Installed power	14 amp
Air pressure	87 psi
Required air	<0.6 NI/p*
Sealing bar	25.20" x 20.08"
Maximum pack height	5.91"
Speed of conveyors	32.81-98.43 ft/min
Speed up to	up to 40 ppm
Max size of film reel	23.50" x Ø13.75"
	85.83" x 60.83"
Machine size	H 60.04" - 65.16"
Machine net Weight	1,279 lbs
Usable films	Polyolefin and Polyethylene



***Lease programs available.

Ask your sales representative for more information



care@hsi.us | www.hsi.us 1-800-394-4426

11515 Vanstory Dr., Ste 145 Huntersville, NC 28078

FP6000 Automatic L-sealer

- Automatic L-sealer
- Sealing bar: 640 x 510 mm
- Maximum pack height: 120 mm (FP6000E)
150 mm (FP6000)
- Motorized conveyor closing system controlled by inverter included (only FP6000)
- Patented film dragging system (only FP6000)

Up to 1800 (FP6000E) - 3000 (FP6000) packs/hour

