# **PeoplePoint<sup>™</sup> Plus**





## The PeoplePoint<sup>™</sup> Plus

### Delivers the flexibility you need

The PeoplePoint Plus is a feature-packed time tracking device with a sleek 7" display. It offers enhanced functionalities like high-fidelity speakers, a wide-angle camera, and a powerful processor. Its biometric technology improves accuracy, while the spacious screen facilitates easy navigation and effective content delivery to your valuable workforce. Additionally, it ensures that employee data is seamlessly collected and sent to the back-end system for streamlined operations.

With its compatibility with multiple identification technologies and seamless data collection capabilities, it provides a comprehensive solution for efficient workforce management.

#### Standard features include:

- Linux based
- Freescale iMX6 1GHz Single core
- 7" Widescreen touch display
- Microphone
- eMMC 8GB storage

To learn more about ATS and the Plus, visit www.accu-time.com or call -1 860.870.5000

## PeoplePoint<sup>™</sup> Plus Terminal Specifications

User Interface CPU Memory	<ul> <li>7" TFT Capacitive Touch, 800 x 480 Resolution</li> <li>20-key tactile, 4x5 matrix <ul> <li>Numeric keypad 0-9</li> <li>Eight software definable function keys</li> <li>Clear/Enter keys</li> </ul> </li> <li>Customizable overlay allows for unique graphic options</li> <li>Freescale iMX6 up to 1GHz (Single Core)</li> <li>1GB DDR3 RAM</li> <li>512MB NAND FLASH</li> </ul>	Corporate Headquarters 20-B International Drive Windsor, CT 06095 TEL: (860) 870-5000 FAX: (860) 872-1511 Toll Free: (800) 355-4648 sales@accu-time.com www.accu-time.com
Mass storage	Non-removable eMMC 8GB, of which 2.0GB are user available	EMEA & APAC
Programming	Linux OS standard. Java™/Python Web services - HTML capable Software Development Kit (SDK)	United Kingdom TEL: +44 (0) 1202 606068
Application software	ATS AccuCollect - Configurable punch workflow management including job transfers, attestations, and more.	All Other Locations TEL: +44 (0) 2920 885599
Communications	Standard 10/100 BASE-T Ethernet Internal USB port Optional Wi-Fi with WPA support Optional internal 3G cellular modem	
Enclosure	PC/ABS	
Power	12 VDC (nominal) 1A, 12W maximum under normal operation Optional uninterruptible power supply Optional IEEE 802.3af/compliant POE	
Environment	Operation Temperature: 0° to 50°C (32° to +122°F) Storage Temperature: -20° to 80°C (-4° to +176°F)	
Dimensions	H 26.67cm x W 22.86cm x D 10.16cm (H 10.5" x W 9" x D 4")	
Certifications	CE Mark, FCC Part 15 Class A	
Accessories	Biometric readers – 1:1 and 1:n Integrated visible or infrared barcode readers Integrated magnetic stripe readers Contactless smartcard readers (HID® Prox, Mifare™, iClass®, Marin) External readers - Wiegand compatible Dry contact low voltage relay modules dual Form C Uninterruptible power supply	



ACCU-TIME SYSTEMS INC.

THE AMERICAS

re about ATS, visit www.accu-time.com or call: 1 (800) 355-4648. As part of Accu-Time's continuous improvement process, we reserve the right to change product specifications without notice. DSTCC

ACCU-TIME SYSTEMS, INC. | PEOPLEPOINT™ PLUS\_PRODUCT INFORMATION SHEFT