



PeoplePoint™ Turbo an Android-based time clock

The Android-based PeoplePoint™ Turbo time clock offers a new level of interaction for employee self-service applications. Designed with data security in mind, the Turbo with its 7" widescreen touch display makes it easy to display HTML5 web-based applications.

As a Value Added Reseller, you can quickly develop your Workforce Management technology and employee self-service applications and deploy them on the PeoplePoint Turbo.

Standard features include:

- Android 5.0 OS
- Freescale iMX6 1GHz Quad Core
- 7" Widescreen touch display
- 2 Speakers
- Microphone
- 16GB storage -eMMC

To learn more about ATS and Turbo, visit www.accu-time.com or call -1 860.870.5000



PeoplePoint™ Turbo Terminal Specifications

User Interface	<ul style="list-style-type: none">• 7" TFT Capacitive Touch, 800 x 480 Resolution• 20-key tactile, 4x5 matrix<ul style="list-style-type: none">» Numeric keypad 0-9» Eight software definable function keys» Clear/Enter keys• Customizable overlay allows for unique graphic options• Microphone and 2 speakers• Camera
CPU	<ul style="list-style-type: none">• Freescale iMX6 up to 1GHz (Quad Core)
Memory	<ul style="list-style-type: none">• 2GB DDR3 RAM• 512MB NAND FLASH
Mass storage	<ul style="list-style-type: none">• Non-removable eMMC• 16GB, of which at least 10GB are user available
Programming	<ul style="list-style-type: none">• Android -based with Android studio• Web services - HTML5
Application software	<ul style="list-style-type: none">• Android-based applications.
Communications	<ul style="list-style-type: none">• Standard 10/100/1000 BASE-T Ethernet• Internal USB port• Optional 4-port USB hub
Enclosure	<ul style="list-style-type: none">• PC/ABS
Power	<ul style="list-style-type: none">• 12 VDC (nominal) 2A, 24W maximum• Optional uninterruptible power supply• Optional IEEE 802.3af/compliant POE module
Environment	<ul style="list-style-type: none">• Operation Temperature: 0° to 50°C (32° to +122°F)• Storage Temperature: -20° to 80°C (-4° to +176°F)
Dimensions	<ul style="list-style-type: none">• H 26.67cm x W 22.86cm x D 10.16cm (H 10.5" x W 9" x D 4")
Certifications	<ul style="list-style-type: none">• CE Mark, FCC Part 15 Class A
Accessories	<ul style="list-style-type: none">• Biometric readers – 1:1 and 1:n• Integrated visible or infrared barcode readers• Integrated magnetic stripe readers• Contactless smartcard readers (HID® Prox, Mifare™, iClass®, Marin)• External readers - Wiegand compatible• Optional external reader - Wiegand compatible• Dry-contact relay modules (Dual Form C, 48V/2A)

ACCU-TIME SYSTEMS INC. THE AMERICAS

Corporate Headquarters
20-B International Drive
Windsor, CT 06095
TEL: (860) 870-5000
FAX: (860) 872-1511
Toll Free: (800) 355-4648
sales@accu-time.com
www.accu-time.com

EMEA & APAC

United Kingdom
TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599

