




|                                |  |
|--------------------------------|--|
| <b>MODULE SIZE</b>             | <p><b>ACTUAL</b><br/>7.5' L x 14' W x 4" H (105 ft<sup>2</sup>)<br/>2.3 m x 4.3 m x 10.16 cm (9.75 m<sup>2</sup>)</p> <p><b>USABLE (DUE TO FLANGE)</b><br/>6.5' L x 13' W x 4" H (84.5 ft<sup>2</sup>)<br/>1.981 m x 3.962 m x 10.16 cm (7.85 m<sup>2</sup>)</p> |
| <b>WEIGHT</b>                  | 1,095 lbs (496.7 kg)   |
| <b>FLANGE THICKNESS</b>        | 2 in (5.08 cm)   |
| <b>COLOR</b>                   | Beige (Custom colors available)  |
| <b>MATERIAL</b>                | High-Density Polyethylene (HDPE) with special impact modifiers that incorporate UV resistance and anti-static properties   |
| <b>WEIGHT LOADING</b>          | 600 psi, depending on subsurface conditions  |
| <b>FLAMMABILITY RESISTANCE</b> | UL94HB   |
| <b>CONNECTION SYSTEM</b>       | Proprietary, self-aligning, aluminum cam S <sup>2</sup> Lock™ system that connects the overlapping flange from adjacent mats with a simple twist of a standard T-bar   |
| <b>SHIPPING INFO</b>           | <p>U.S. standard 48 ft. flatbed truck: 40 mats</p> <p>40 ft ISO shipping container: 40 mats</p> <p>20 ft ISO shipping container: 20 mats – 1 stack, 20 full mats high</p> <p>U.K. lorry/EU trucks: Up to 50 mats</p>   |

3AMD 200408 ©2020 Signature Systems