



PRODUCT SPECIFICATIONS

RAMP SPECIFICATIONS



	PRODUCT SPECIFICATIONS	RAMP SPECIFICATIONS
MODULE SIZE	<p>ACTUAL 4' x 4' x 1.5"</p> <p>NET WORKING SURFACE: 13.5 ft² (1.25 m²)</p>	43.75" x 18" x 1.5"
WEIGHT	50 lbs (22.68 kg)	13.5 lbs
COMPRESSION STRENGTH	450 psi (3,100 kps)	
MAX WHEEL LOAD	300 psi (2,068 kps)	
MAX ALLOWABLE DEFLECTION	3 in (7.62 cm)	
COLOR	Translucent white or grey	
MATERIAL	Virgin HDPE Plastic	Virgin HDPE Plastic
TEMPERATURE RANGE	-4° F – 113° F (- 20° C – 45° C)	
BURN RATING	UL 94-HB	
DESIGN FEATURES	Diamond surface texture, closed-back design, overlapping/underlapping flanges enhance load spread and create a smooth surface	Female and male configuration adjoin with appropriate edge of the panels. Pairs of panels are used to create build joints. Meets ADA compliance requirements (US).
CONNECTION SYSTEM	Preinstalled nylon cam locks; vertical locking system – no loose parts T-bar locking tool	
SHIPPING CAPACITY	US Standard 48 ft flatbed truck: 840 panels/11,340 ft ² (1053.52 m ²)	

©2021 Signature Systems



US +1 972-332-4337 | UK +44 1642 744950

signature-systems.com