

Panel Cutout ٦∟ $\overline{\Phi}$ 3.15 ±.010 2.76 ±.004 [80.0 ±0.2] [70.0 ±0.1] 8.52 Ф [216.4] 0 <MOD-DIAM>0.26 +.010 4.80 ±.010 • ⊕ [6.5 + 0.2][122.0 ±0.2] 5.83 ±.004 TYPE [148.0 ±0.1] <MOD-DIAM>0.45<HOLE-SPOT>0.20 (\$0.00 kg [11.5<HOLE-SPOT>5.5] 6.50 ⊚ [165.0] <MOD-DIAM>0 .26 ±.004 $[6.5 \pm 0.1]$ [14.4] \odot (\bigcirc) /// 3.78 96.0 0 5.02 [127.6] 0.43 1.60 [11.0] [40.7]

NOTE:

- 1) REFER TO INSTALLATION INSTRUCTIONS TO ENSURE PROPER INSTALLATION.
- 2) ALWAYS FOLLOW YOUR LOCAL/FACILITY ELECTRICAL CODES AND PROCEDURES.
- 3) FOR DETAILED COMPONENT WIRING AND SPECIFICATIONS, REFER TO THE APPLICABLE DATA SHEETS.
- 4) COMPONENT LOCATIONS OUTLINED IN DRAWING ARE APPROXIMATE
- 5) FOR ACTUAL PRODUCT CONFORMITY, LISTINGS AND CERTIFICATIONS, REFER TO FINISHED PRODUCT FACEPLATE DRAWING, OR CONSULT FACTORY.

