



Spectrum Management and Telecommunications

Supplementary Procedure

Supplementary Procedure for Assessing Specific Absorption Rate (SAR) and Absorbed Power Density (APD) Compliance of Portable Devices in the 6 GHz Band (5925-7125 MHz)

DRAFT

Preface

This Innovation, Science and Economic Development Canada compliance procedure describes the technical requirements and processes to be followed when demonstrating compliance with specific absorption rate (SAR) limits and absorbed power density (APD) limits for portable devices operating in the 6 GHz band (e.g. RLAN device in the 5925- 7125 MHz)

Issued under the authority of the Minister of Innovation, Science and Industry

MARTIN PROULX
Director General
Engineering, Planning and Standards Branch

DRAFT

Table of Contents

1. Scope	1
3. Normative references	1
4. Definitions and abbreviations	2
4.1. Definitions.....	2
4.2. Abbreviations and acronyms	2
5. RF exposure compliance assessment approach	3
6. Preparation of the DUT	3
6.1. Configurations to be tested.....	3
7. Measurements	4
7.1. Measurement system requirements	5
7.2. System validation and system check	5
7.3. Uncertainty evaluation	5
7.4. Measurement of devices with multiple antennas or multiple transmitters	6
8. RF exposure technical brief	8
Annex A: Bibliography	9

1 **1. Scope**

2 Supplementary Procedure SPR-APD, issue 1, for Radio Standards Specification RSS-102, [Radio](#)
3 [Frequency \(RF\) Exposure Compliance of Radiocommunication Apparatus \(All Frequency Bands\)](#),
4 sets out the general test methods to be followed when carrying out a SAR and APD compliance
5 assessment of portable devices overlapping the 6 GHz frequency band that are subject to RSS-248
6 entitled [Radio Local Area Network \(RLAN\) Devices Operating in the 5925-7125 MHz Band](#).

7 **2. Certification requirements**

8 All testing performed to demonstrate RF exposure compliance of RLAN devices operating in the
9 5925-7125 MHz band shall be carried out by an ISED-recognized testing laboratory. To perform
10 APD assessments, the testing laboratory shall have, at a minimum, the **RSS-102 (SAR)**^{MEAS} scope.
11 To perform RF exposure assessments, the testing laboratory shall have, at a minimum, the **RSS-**
12 **102 (RF Exp.)**^{MEAS} scope.

13 **3. Normative references**

14 The following documents shall be consulted for the application of SPR-APD. The most recent
15 versions of these reference publications shall be used for showing compliance.

- 16 • Radio Standards Specification RSS-102, [Radio Frequency \(RF\) Exposure Compliance of](#)
17 [Radiocommunication Apparatus \(All Frequency Bands\)](#)
- 18 • International Electrotechnical Commission (IEC) 62209-1528, [Measurement procedure](#)
19 [for the assessment of specific absorption rate of human exposure to radio frequency](#)
20 [fields from hand-held and body-worn wireless communication devices - Human models,](#)
21 [instrumentation and procedures \(Frequency range of 4 MHz to 10 GHz\)](#)
- 22 • Safety Code 6, [Limits of Human Exposure to Radiofrequency Electromagnetic Energy in](#)
23 [the Frequency Range from 3 kHz to 300 GHz](#)
- 24 • Safety Code 6 Notice, [Localized human exposure limits for radiofrequency fields in the](#)
25 [range of 6 GHz to 300 GHz](#)
- 26 • FCC KDB 248227 D01, [SAR guidance for IEEE 802.11 \(Wi-Fi\) Transmitters](#)

27 ISED may consider assessment methods not covered by SPR-APD or the referenced
28 publications. Consult ISED’s [Certification and Engineering Bureau](#) website to determine the
29 acceptability of any alternative measurement methods, or send an inquiry by [email](#) with detailed
30 information on the alternative assessment method(s).

31 **4. Definitions and abbreviations**

32 This section contains definitions for terms used throughout this document, as well as
33 explanations for acronyms and abbreviations used herein.

34 **4.1. Definitions**

35 **Absorbed power density (APD) evaluation:** The method used to evaluate APD levels from a
36 device by physical measurement. An APD evaluation is required for devices operating at a
37 frequency greater than 6 GHz and if the separation distance between the user or bystanders and
38 the device is less than or equal to 20 cm.

39 **Averaging area:** The area on the evaluation surface over which the APD or SAR is averaged.
40 For SAR assessments in the 6 GHz band, 1g or 10g tissue volume is used for head/neck/trunk and
41 limbs respectively. For APD assessments in the 6 GHz band, the averaging area is defined as a 4cm²
42 square. This is equivalent to 8g tissue volume.

43 **Specific absorption rate (SAR) evaluation:**

44 The method used to evaluate SAR levels from a device by physical measurement or
45 computational modelling techniques. A SAR evaluation is required for devices operating at a
46 frequency less than or equal to 6 GHz and if the separation distance between the user or
47 bystander and the device is less than or equal to 20 cm.

48 **4.2. Abbreviations and acronyms**

49 This document uses the following abbreviations and acronyms:

50 APD absorbed power density

51 DUT device under test

52 FCC Federal Communications Commission

53 IEC International Electrotechnical Commission

54 IEEE Institute of Electrical and Electronics Engineers

55 ISED Innovation, Science and Economic Development Canada

56 KDB Knowledge database

57 MEAS measurement

58 PD power density

59 pPD peak power density (as defined in [SPR-003](#))

60 psPD peak spatial power density (as defined in [SPR-003](#))

- 61 SAR specific absorption rate
- 62 TER total exposure ratio (TER)

63 **5. RF exposure compliance assessment approach**

64 RF exposure compliance shall be demonstrated based on Health Canada's [Safety Code 6 limits](#)
65 [adopted in RSS-102 entitled Radio Frequency \(RF\) Exposure Compliance of Radiocommunication](#)
66 [Apparatus \(All Frequency Bands\)](#). As set forth in [RSS-102](#), RF exposure compliance of devices
67 meant to be used less than or equal to 20 cm from a user and/or bystander shall be assessed against
68 the basic restriction limits. Conversely, RF exposure compliance of devices meant to be used at
69 distances greater than 20 cm shall be assessed by an [RF exposure evaluation](#) against the reference
70 level limits.

71 For RLAN devices operating in the 5925 MHz-7125 MHz band, the same requirements apply:

72 Devices operating less than or equal to 20 cm from a user and/or bystander:

- 73 • From 5925 MHz to 6000 MHz, RF exposure compliance shall be assessed against the SAR
74 limits (basic restrictions) as defined in [RSS-102](#).
- 75 • Above 6000 MHz, RF exposure compliance shall be assessed against APD limits defined by
76 Health Canada's [Notice](#), and adopted in [RSS-102](#).
- 77 • For frequency channels which occupy bandwidth above and below 6000 MHz, both the SAR
78 and APD limits apply.

79 Devices operating at distances greater than 20 cm from a user and/or bystander:

- 80 • These devices shall continue to be tested according to the requirements and procedures set
81 forth in [RSS-102](#).

82 **6. Preparation of the DUT**

83 The preparation of the DUT, including the test positions and configurations shall be based on
84 [RSS-102](#) and its accepted test procedures incorporated by reference, including [IEC/IEEE 62209-](#)
85 [1528](#) and FCC KDB 248227 D01. Some requirements are introduced for the test frequencies and
86 channels in the following sub-section.

87

88 **6.1. Configurations to be tested**

89 The configurations to be tested shall be based on FCC KDB 248227 D01.

90

91 The maximum output power, including tune-up tolerance, is used to determine the initial test
 92 configuration. When the same maximum power is specified for multiple transmission modes in a
 93 frequency band, the initial test configuration shall start with the largest channel bandwidth,
 94 lowest order modulation, lowest data rate. The subsequent test configurations, including the test
 95 reduction procedures, shall follow the aforementioned FCC KDB.

96
 97 For APD, the following conversion factors apply for the threshold for test reductions:

- 98 • 0.4 W/kg is equivalent to 25% of the APD limits: 5 W/m²;
- 99 • 0.8 W/kg is equivalent to 50% of the APD limits: 10 W/m²; and
- 100 • 1.2 W/kg is equivalent to 75% of the APD limits: 15 W/m².

101
 102 Using the methodology and formula in section 7.2.8 of IEC/IEEE 62209-1528, the minimum
 103 number of test frequencies shall be 5 provided the number of possible channels is greater than 5.
 104 In all cases, the lowest channel shall be tested. When any part of the lowest channel spans across
 105 6000 MHz, compliance to both the SAR and APD limits shall be demonstrated.

106 Table 1: Minimum number of test frequencies required

Channel Bandwidth (MHZ)	Number Possible Channels	Minimum Number of Test Frequencies
320	3	3
160	7	5
80	14	5
40	29	5
20	60	5

107
 108 As an example of the application of the above table, if we assume the device operates using 80
 109 MHz channels, there are 14 possible channels between 5925 and 7125 MHz. For the purposes of
 110 testing, a minimum of 5 test frequencies shall be used. The test frequencies should represent the
 111 entire frequency range and be evenly spaced representing the low, middle and high portion of the
 112 band.

113 **7. Measurements**

114 While SAR assessments have been established for many years, APD assessments are relatively
 115 new. A scientific journal recently published that the APD may be derived from SAR
 116 measurements (see [Compliance Assessment of the Epithelial or Absorbed Power Density Below 10 GHz Using SAR Measurement Systems](#) for details). As a result, measurement systems capable
 117 of assessing SAR may be used to assess APD provided they implement algorithms (see section
 118 7.1) allowing the conversion from SAR to APD.
 119

120 **7.1. Measurement system requirements**

121 APD shall be assessed with a SAR measurement system which complies with all the requirements
122 in [RSS-102](#) and the [IEC/IEEE 62209-1528](#) international standard.

123 The APD shall be derived from the measured SAR values using the formulas in the [Compliance](#)
124 [Assessment of the Epithelial or Absorbed Power Density Below 10 GHz Using SAR Measurement](#)
125 [Systems](#) document.

126 The APD evaluation shall be based on the same measurement procedure as defined in [RSS-102](#)
127 and [IEC/IEEE 62209-1528](#) for SAR but with modifications to the uncertainty evaluation (see
128 section 7.3) to account for the conversion from SAR to APD.

129 **7.2. System validation and system check**

130 The system validation and system check shall continue to be performed as per [IEC/IEEE 62209-](#)
131 [1528](#). The numerical SAR target values found in Table D.2 of that document shall continue to
132 apply. In addition, the following target values shall be used for standard dipoles and flat
133 phantoms.

134 Table 2: System validation target values

Frequency (MHz)	1g SAR (W/kg)	8g SAR (W/kg)	10g SAR (W/kg)	4 cm ² APD (W/m ²)
6500	298.4	64.6	52.8	1290
7000	275.0	59.7	47.0	1190

135

136 Above 6000 MHz, for successful system validation, step a) of Annex A.3.5 of the [IEC/IEEE](#)
137 [62209-1528](#) shall be used for the 8g SAR values, which is equivalent to 4 cm².

138 The system check and measured system validation values shall be reported in the RF exposure
139 technical brief.

140

141 **7.3. Uncertainty evaluation**

142 Measurement equipment manufacturers shall provide all associated uncertainty components for
143 the conversion of SAR to APD. They shall be added to the uncertainty budget table specified in
144 section 8 of the [IEC/IEEE 62209-1528](#). The updated uncertainty budget shall be provided in the
145 RF exposure technical brief submitted to ISED in the certification filing.

146

147 **7.4. Measurement of devices with multiple antennas or multiple transmitters**

148 When an operational mode is capable of multiple simultaneous transmissions, operating in bands
 149 other than the 6 GHz frequency band, this operational mode shall also be tested using procedures
 150 outlined in [RSS-102](#) and its associated SPRs.

151 A conservative way to assess compliance with the RF exposure limits is to evaluate the
 152 corresponding TER, which can be expressed as:

153
$$TER_{SAR-PD} = \sum_{n=1}^N ER_{SAR,n} + \sum_{m=1}^M ER_{PD,m} + \sum_{k=1}^K ER_{EH-SAR,k}$$

154 where:

- 155
- 156 • TER_{SAR-PD} is the SAR-PD based TER
 - 157 • N is the total number of transmitters for which a SAR assessment has been performed
 - 158 • $ER_{SAR,n}$ is the exposure ratio contribution from the n -th transmitter for which a SAR
 159 assessment has been performed
 - 160 • M is the total number of transmitters for which a PD and/or APD assessment has been
 161 performed;
 - 162 • $ER_{PD,m}$ is the exposure ratio contribution from the m -th transmitter for which a PD
 163 and/or APD assessment has been performed
 - 164 • K is the total number of transmitters for which an assessment against the SAR-based
 165 reference levels for the incident E- and H-fields has been performed
 - 166 • $ER_{EH-SAR,k}$ is the exposure ratio contribution from the k -th transmitter for which an
 167 assessment against the SAR-based reference levels for the E- and H-fields has been
 168 performed

169 The exposure ratio resulting from a SAR assessment can be expressed as:

170
$$ER_{SAR,n} = \frac{SAR_n}{SAR_{BR,n}}$$

171 where:

- 172
- 173 • SAR_n is the SAR value for the n -th transmitter/test frequency
 - 174 • $SAR_{BR,n}$ is the basic restriction for SAR that is applicable to the n -th transmitter/test
 175 frequency

176 For transmitters operating above 6000 MHz, it is necessary to perform an assessment against the
177 PD (basic restriction up to 10 GHz and reference levels beyond). The exposure ratio for the m -th
178 transmitter is given by:

$$179 \quad ER_{PD,m} = \begin{cases} \max \left[\frac{SAR_m}{SAR_{BR,m}}, \frac{APD_m}{APD_{BR,m}} \right], & 5925 \text{ MHz} < f_m \leq 7125 \text{ MHz} \\ \frac{psPD_m}{psPD_{RL,m}}, & 7125 \text{ MHz} < f_m \leq 30 \text{ GHz} \\ \max \left[\frac{psPD_m}{psPD_{RL,m}}, \frac{pPD_m}{pPD_{RL,m}} \right], & f_m > 30 \text{ GHz} \end{cases}$$

180 where:

- 181
- 182 • SAR_n is the SAR value for the n -th transmitter/test frequency
- 183 • $SAR_{BR,n}$ is the basic restriction for SAR that is applicable to the n -th transmitter/test
- 184 frequency
- 185 • APD_m is the APD value for the m -th transmitter/test frequency
- 186 • $APD_{BR,m}$ is the basic restriction for APD that is applicable for the m -th transmitter/test
- 187 frequency
- 188 • $psPD_m$ is the psPD value for the m -th transmitter
- 189 • $psPD_{RL,m}$ is the applicable psPD reference level for the m -th transmitter
- 190 • f_m is the operating frequency of the m -th transmitter
- 191 • pPD_m is the pPD value for the m -th transmitter
- 192 • $pPD_{RL,m}$ is the applicable pPD reference level for the m -th transmitter

193

194 When taking into account contributions from transmitters operating below 10 MHz, it is
195 necessary to perform an assessment against the SAR-based reference levels for the incident E-
196 and/or H-fields. The corresponding exposure ratio is given as:

$$198 \quad ER_{EH-SAR,k} = \begin{cases} \left(\frac{H_{SAR,k}}{H_{RL-SAR,k}} \right)^2, & 100 \text{ kHz} \leq f_k < f_{env} \\ \max \left[\left(\frac{E_{SAR,k}}{E_{RL-SAR,k}} \right)^2, \left(\frac{H_{SAR,k}}{H_{RL-SAR,k}} \right)^2 \right], & f_{env} \leq f_k < 10 \text{ MHz} \end{cases}$$

199 where:

- 200
- 201
- 202
- 203
- 204
- 205
- 206
- 207
- 208
- 209
- 210
- 211
- 212
- $H_{SAR,k}$ is the root-mean-square (RMS) incident H-field from the k -th transmitter, time-averaged in accordance with a SAR-based assessment
 - $H_{RL-SAR,k}$ is the SAR-based reference level for the incident H-field which is applicable to the k -th transmitter
 - f_k is the operating frequency of the k -th transmitter
 - $E_{SAR,k}$ is the RMS incident E-field from the k -th transmitter, time-averaged in accordance with a SAR-based assessment
 - $E_{RL-SAR,k}$ is the SAR-based reference level for the incident E-field that is applicable to the k -th transmitter
 - f_{env} is 1.10 MHz when considering the limits for uncontrolled environments and 1.29 MHz when considering the limits for controlled environments, as per Health Canada's Safety Code 6

213 Compliance with the SAR-PD based RF exposure limits is achieved if $TER_{SAR-PD} \leq 1$.

214 Situations where the TER exceeds unity shall be reported to ISED. Alternative methods

215 considering point-by-point evaluations may be considered on a case-by-case basis. The TER

216 shall be documented in the RF exposure technical brief.

217

218 It is also important to demonstrate compliance with the exposure limits to prevent nerve

219 stimulation. However, the assessment is performed separately and the resulting exposure ratios

220 are not added to the TER_{SAR-PD} .

221 **8. RF exposure technical brief**

222 In addition to the requirements set forth in [section 2.2](#) of RSS-102, the RF technical brief shall

223 also include the:

- 224
- 225
- 226
- 227
- uncertainty budget calculations as defined in section 7.3, and
 - system check values above 6 GHz;
 - system validation values above 6 GHz.

228 **Annex A: Bibliography**

229 The following documents were consulted in the preparation of this supplementary procedure:

230 Samaras, T., Christ A., and Kuster, N. (2021). “[Compliance Assessment of the Epithelial or](#)
231 [Absorbed Power Density Below 10 GHz Using SAR Measurement Systems](#)” Bioelectromagnetics,
232 online June 15, 2021

233 International Electrotechnical Commission *Conversion Method of Specific Absorption Rate to*
234 *Absorbed Power Density for the Assessment of Human Exposure to Radio Frequency*
235 *Electromagnetic Fields from Wireless Devices in Close Proximity to the Head and Body –*
236 *Frequency Range of 6 GHz to 10 GHz* (Draft)

237