

## Datasheet **ValkBox Boltline**

### The concept

- All loose mounting materials packaged in one box
- Profiles available in lengths of 2185 mm and 1122 mm for efficient transport
- Configurations of two to five panels
- Full-black finishing of visible parts
- Portrait and landscape mounting possible

### Unique features

- Maximal ease of ordering
- Maximal ease of logistics, optimisation of stock
- Maximal ease of mounting, pre-mounted parts
- Minimal cost due to efficient transport

### Roof mounting

- Hanger bolt with L-adaptor and hammer head screw – fixed in concrete

### Technical specifications

- Suitable for panel size: circa 1650 mm x maximal 1005 mm x 28-50 mm
- Possibility to adjust the profiles vertically (if roof sags)
- Universal mid- and end panel clamps (28-50 mm)
- Maximal roof height of 9 m
- Roof pitch: 45°

### Extension kit

To accommodate panels from 2230 x 1150 mm at the ValkBox Boltline the profiles should be extended. For this you need per box two Alu coupling for Side++ profile (724863) and two Alu. Side++ profile L=300 mm (701700300).


### Mounting

- Easily calculate the number of anchor points with the ValkPVplanner
- Screw depth
- Edge clearance
- L-adaptor

### Example of project calculation

Required number and type of ValkBoxes for a roof with 1 row of 3 panels and 1 row of 5 panels (vertical mounting):

- 1 x ValkBox - Boltline Roofs 3
- 1 x ValkBox - Boltline Roofs 5
- 3 profiles with a length of 2185 mm and 2 with a length of 1122 mm



### CONTACT DETAILS | DEVELOPER AND PRODUCER OF SOLAR MOUNTING SYSTEMS

#### Van der Valk Solar Systems + International

Westernesse 18 - 2635 BG Den Hoorn, The Netherlands  
 +31 174 25 49 99  
 sales@valksolarsystems.com

#### Valk Solar Systems UK + IE

+44 1304 89 76 58  
 sales@valksolarsystems.co.uk

#### Valk Solar Systems Ibérica

+34 699 326 544  
 ventas@valksolarsystems.es

#### Valk Solar Systems Nordics

+46 7 24 41 60 82  
 sales@valksolarsystems.se