



# Advantage® OptiSeal Sealing Primer

## Technical Data Sheet

## Advantage® OptiSeal Sealing Primer

Unique primer which can be applied directly after final rinse to encapsulate asbestos fibres immediately and seal porous surfaces. Solvent free two component water based primer with excellent adhesion to asbestos.

### In Liquid Form

Feature	Result
Specific Weight:	1.2 gr/cm <sup>3</sup>
Application Temperature:	5°C to +35°C
Touch Dry:	4 Hours
Overcoat Time:	Overnight to maximum 3 days
Volume Solids:	52% typical
VOC:	0 g/Lt - VOC Free
Flash Point:	n/a
Mixing Ratio:	2 parts base: 1 part activator

### General Information

Feature	Result
Shelf Life:	2 years minimum in unopened tins in a cool dry place out of direct sunlight
Coverage:	Theoretical minimum consumption is 10-14m <sup>2</sup> per 1L in one coat depending on substrate
Pack Sizes:	5 Litres
Colour:	White
Thinning:	Do not thin
Brush Wash:	Clean water



Alltimes Coatings, Units C & D,  
Station Road Industrial Estate,  
South Woodchester, Stroud,  
Gloucestershire. GL5 5EQ. UK

T: 01453 872 850

E: [info@alltimescoatings.co.uk](mailto:info@alltimescoatings.co.uk)

W: [www.alltimescoatings.co.uk](http://www.alltimescoatings.co.uk)

*No responsibility can be taken by the manufacturers where conditions of use are beyond our control. All products should be used in accordance with the manufacturer's instructions. For further information please refer to the application guide and Material Safety Data Sheet. This information and guidance is given in good faith and without prejudice and liability, Technical and Safety Data must be observed. All coverages are given as a guide only, as volumes will vary with profile, porosity and method of application. Loss factors should also be taken into account.*