

# **3D CLEANING CHAINS**

#### **Expand Your Cleaning Options**



At Picote, we are constantly looking for ways to work smarter so your hard work goes further. The new self-adjusting 3D Cleaning Chains were designed to exchange setup time for working time making a cleaner, faster, and more efficient job site.

Gone are the days of changing tools every time the pipe size changes or adjusting the chain size during descaling. Thanks to a shape-shifting design, you can now use one tool to do the job of several. This exciting new innovation in drain cleaning is patent-pending.



Two models available: The Premium version features the proven, superior performance of our star-carbide teeth, while the PVC version is the safer choice when the condition of the original host pipe material is unknown to allow you to safely remove blockages and restore flow.

### **USES AND BENEFITS**

Our pursuit of innovation means we are always pushing the boundaries of what can be achieved with our tools and the 3D chains take high speed drain cleaning to the next level.

- Come on a pre-built leader making them easier to use and decreasing shaft wear.
- Self-adjusting depending on RPM. Great for diameter changes where access is limited.
- No need to readjust during descaling; the 3D chain will keep expanding as it removes material until it reaches its maximum size.
- We test all of our products extensively both in our R&D center and the field before they ever see the market.

3D Cleaning Chain Technical Specifications		
Shaft Size	Pipe Size	
8mm (1/3")	DN50-75 (2-3")	
	DN70-100 (3-4")	
12 mm (1/2")	DN70-100 (3-4")	
S-10 - 32	DN100-150 (4-6") for Premi	ium Chain Only
Pipe Material	Cast Iron, Concrete, Clay, PVC	
Operational Guide - Rotation Speed & Chain Opening		
Chain	Rotation Speed	Shaft Size
DN50-75 (2-3")	Level 2 - DN50 (2")	8 mm (1/3")
	Level 4 - DN70/75 (3")	8 mm (1/3")
DN70-100 (3-4")	Level 2 - DN70/75 (3")	8 mm (1/3")
	Level 3 - DN100 (4")	8 mm (1/3")
DN70-100 (3-4")	800 rpm - DN70/75 (3")	12 mm (1/2")
	1250 rpm - DN100 (4")	12 mm (1/2")
DN100-150 (4-6")	800 rpm - DN100 (4")	12 mm (1/2")
	1100 rpm - DN150 (6")	12 mm (1/2")
<b>Note!</b> Always select rotation speed according to chain opening / rotation speed table from above when working inside fragile or otherwise brittle cast iron pipes. If the host pipe is intact, higher		









rotation speed can be used.



## More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Grinding Chains Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

#### **PRODUCTS & SPARE PARTS**





3D Cleaning Chain Product List		
PN	Description	
Premium Chain with leader for 8mm (1/3") shaft		
1382005070	3D Premium Chain Package DN50-75 (2-3")	
1382070100	3D Premium Chain Package DN70-100 (3-4")	
Premium Chain with leader for 12mm (1/2") shaft		
1383070100	3D Premium Chain Package DN70-100 (3-4")	
1383100150	3D Premium Chain Package DN100-150 (4-6")	
Spare parts: Premium 3D Chain only		
1380084050D	3D Premium Chain DN50-75 (2-3") for 8mm (1/3") shaft	
1380084070D	3D Premium Chain DN70-100 (3-4") for 8mm (1/3") shaft	
1380125070D	3D Premium Chain DN70-100 (3-4") for 12mm (1/2") shaft	
1380125100D	3D Premium Chain DN100-150 (4-6") for 12mm (1/2") shaft	
PVC Chain with leader for 8mm (1/3") shaft		
1382005070P	3D PVC Chain Package DN50-75 (2-3")	
1382070100P	3D PVC Chain Package DN70-100 (3-4")	
PVC Chain with leader for 12mm (1/2") shaft		
1383070100P	3D PVC Chain Package DN70-100 (3-4")	
Spare parts: PVC 3D Chain only		
1380084050DP	3D PVC Chain DN50-75 (2-3") for 8mm (1/3") shaft	
1380084070DP	4070DP 3D PVC Chain DN70-100 (3-4") for 8mm (1/3") shaft	
1380125070DP	3D PVC Chain DN70-100 (3-4") for 12mm (1/2") shaft	







