

PICOTE MAXI POWER+

The Largest and Most Powerful Miller



The Maxi Power+ is designed for even higher performance cleaning, lining removal, and cutting/reinstatements in larger diameter pipes.

It provides nearly double the power of a Maxi Miller for pipe cleaning, descaling, and root removal in DN70-300 (3-12") pipes.

Reinstatements in DN150-300 (6-12") pipes. It can also be used for concrete, slurry, and rock removal in DN150-220 (6-9") pipes.

It has a working range of 18m (60'), but that can be lengthened by as much as 22m, or 72 feet, by using up to two shaft extensions.

USES AND BENEFITS

- The Maxi Power+ has unique power requirements and should be run off the 400 Volt, 3-phase Picote Generator, or a comparable unit.
- High Speed/High Torque: 500-1500 rpm.
- Standard safety features include: protective outer shaft casing, operator presence foot control, electric safety clutch, internal GFI, and an emergency stop to help keep you and your equipment investment protected.



Picote Generator

Maxi Miller Power+ Technical Specifications

Pipe Size Ranges	
Cleaning / Descaling	DN100-300 (3-12")
Cutting / Reinstatement	DN75-300 (3-12")
Concrete, Grout, Slurry Removal	DN150-225 (6-9")
Usable Shaft Length	18m (60')
Shaft Extensions	11m (36')
Shaft Size	18mm (¾")
Casing Type	Thick
Output Power	3.0kW
Speed	500-1500 RPM
Power Source	US/UK: 400V, 3-Phase, 30/16 Amp
Maxi Power+ Weight	113kg (249 lbs)
Control Box Weight	16kg (35 lbs)
Size	1150 x 854 x 489mm
	45 x 34 x 19"
Safety Features	Protective outer shaft casing, operator presence foot control, internal GFI, electric safety clutch, and emergency stop.
IP Class	54

More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Maxi Miller Power+ Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in the USA, UK, and Finland.

PRODUCTS AND SPARE PARTS

Picote Maxi Miller Power+ Products and Parts	
PN	Description
3570032018	Maxi Miller Power+
3570032018UK	Maxi Miller Power+ UK
3570032018US	Maxi Miller Power+ US
1350000022	Picote Generator 400v
1350000022UK	Picote Generator 400v UK
1350000022US	Picote Generator 400v US
3570032118	Maxi Miller Power+ & 400v Picote Generator
3570032118UK	Maxi Miller Power+ & 400v Picote Generator UK
3570032118US	Maxi Miller Power+ & 400v Picote Generator US
Spare Parts	
1312021180020	Maxi Miller Power+ Replacement Shaft - 18mm (¾") 20m (67')
3212323195	Outer casing for 18mm (¾") shaft
1350000020	Picote Flexible Shaft Lubricant bottle (0.5 litres/17oz)
1350000021	Picote Flexible Shaft Lubricant package (6 bottles)