

SMART HEAT MILLERS & CABLES

Safely Speedup & Ensure Ambient CIPP Curing



The Picote Smart Heat Millers make your ambient CIPP curing process up to 35% faster to help ensure completion according to the resin curing schedule.

With worksite proven technology, this easy to use and ecological friendly option doesn't use water, so there is no risk of water damage inside buildings.

Especially helpful for situations where low temperatures might make ambient curing challenging - such as hidden pipes, air vents, or pipes located in attics.

Three models available: Maxi & Mini Smart Heat Millers and stand-alone Smart Heat Cables.

USES AND BENEFITS

- The Mini Smart Heat is built on a customized Picote Mini Miller frame. It is small and compact making it excellent for use inside buildings. It has 15m (50') of heat cable.
- The Maxi Smart Heat is built on a customized Maxi Miller frame with 30m (98') of heat cable. It is ideal for jobs with hidden pipes or pipes outside of buildings.
- The separate Smart Heat Cables can be used for curing assistance on shorter projects of 5, 8, & 10m (16, 25, & 32'). These are manufactured to be used with the Max Smart Heat Curing Caps.

Smart Heat Miller Technical Specifications	
Temperature	60-70°C (140-158°F) when curing inside the lining
Safety Features	Emergency stop, internal GFI
Mini Smart Heat Miller	
Range	15m (50')
Power	UK/US: 110/125V, 15 Amp EU: 220/230V, 16 Amp
Output (W)	1050W
Weight	22kg (49 lbs)
Size	752 x 519 x 389mm 29 x 20 x 16"
Maxi Smart Heat Miller	
Range	30m (98')
Power	UK/US: 110/125V, 30 Amp EU: 220/230V, 16 Amp
Output (W)	2100W
Weight	53kg (117 lbs)
Size	1150 x 854 x 489mm 45 x 34 x 19"
Smart Heat Cables	
Range	5, 8, & 10m (16, 25, & 32')
5m (16') Output (W)	320W
10m (32') Output (W)	640W
Power Cord Length	2m (6½')
Cable Diameter	21mm (1¾")

More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Smart Heat Miller Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS & SPARE PARTS

Smart Heat Miller Products and Parts (US)	
PN	Description
3410000000US	Mini Smart Heat Miller US
3430000000US	Maxi Smart Heat Miller US
3430000005US	Smart Heat Cable 5m (16') - US
3430000007US	Smart Heat Cable 7.6m (25') - US
3430000010US	Smart Heat Cable 10m (33') - US
2340004050US	Mini Smart Heat Curing Cap DN50 (2") US
2340004070US	Mini Smart Heat Curing Cap DN75 (3") US
2340004100US	Mini Smart Heat Curing Cap DN100 (4") US
2340005050US	Maxi Smart Heat Curing Cap DN50 (2") US
2340005070US	Maxi Smart Heat Curing Cap DN75 (3") US
2340005100US	Maxi Smart Heat Curing Cap DN100 (4") US
Smart Heat Miller Products and Parts (EU & UK)	
PN	Description
3410000000	Mini Smart Heat Miller
3430000000	Maxi Smart Heat Miller
3430000005	Smart Heat Cable 5m (16')
3430000010	Smart Heat Cable 10m (33')
3410000000UK	Mini Smart Heat Miller - UK
3430000000UK	Maxi Smart Heat Miller - UK
3430000005UK	Smart Heat Cable 5m (16') - UK
343000010UK	Smart Heat Cable 10m (33') - UK
2340004050	Mini Smart Heat Curing Cap DN50 (2")
2340004070	Mini Smart Heat Curing Cap DN70 (3")
2340004100	Mini Smart Heat Curing Cap DN100 (4")
2340005050	Maxi Smart Heat Curing Cap DN50 (2")
2340005070	Maxi Smart Heat Curing Cap DN70 (3")
2340005100	Maxi Smart Heat Curing Cap DN100 (4")