

## TWISTER CONCRETE REMOVER+

*For the Toughest Concrete, Grout, Slurry, & Rock Removal Work*



Front  
Panel



Flat Front  
Drill Head



Steering  
Axle

The Twister Concrete Remover+ has dual front brushes for added stability, a heavy duty front panel with large carbides, and a specialized front drill head with star carbides, all of which combine for efficient concrete, grout, slurry, & rock removal.

The front drill head vibrates removing more material and making a bigger hole in front to decrease the risk of the tooling getting stuck.

The optional steering axle can allow steering with the help of a steering wire. This is especially helpful in working in bends - provided the pipe is not completely full of concrete.

## USES AND BENEFITS

- Recommended for the toughest removal work paired with the Maxi Miller Power+.
- Save costly excavation to remove concrete, grout, slurry, and large rocks from pipes.
- Can also grind offsets in clay and concrete pipes prior to CIPP lining for a superior finish.

### Twister Concrete Remover+ Technical Specifications

#### Compatible Millers, Pipe Sizes, & Options:

Millers:	Maxi Power+
Pipe Sizes:	DN150, 200, & 225 (6, 8, & 9")
Optimal Rotation Speed	1000-1200 (normally)

## More Info/Guides/Technical Support:

- Visit [picoteinstitute.com](http://picoteinstitute.com) for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Twister Concrete Remover+ Operation & Safety Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

## PRODUCTS & SPARE PARTS

Twister Concrete Remover+ Product List	
PN	Description
1234130150	Twister Concrete Remover+ DN150 (6")
1234175200	Twister Concrete Remover+ DN200 (8")
1234200225	Twister Concrete Remover+ DN225 (9")
1234130150SA	Twister Concrete Remover+ DN150 (6") with Steering Axle
1234175200SA	Twister Concrete Remover+ DN200 (8") with Steering Axle
1234200225SA	Twister Concrete Remover+ DN225 (9") with Steering Axle
Spare Parts	
PN	Description
1300215057	Front Drill Head Twister Concrete+ 60mm (2 $\frac{3}{8}$ ")
1210510130	Front Metal Panel 130mm (5 $\frac{1}{8}$ "), g6, 3mm, Twister Concrete+
1210510175	Front Metal Panel 175mm (6 $\frac{7}{8}$ "), g6, 3mm, Twister Concrete+
1210510200	Front Metal Panel 200mm (8"), g6, 3mm, Twister Concrete+
1100100055	Steering Axle - 55mm (2 $\frac{5}{32}$ ")
1100200001	Bearing for Steering Axle